



JUMBO TANKS

Jumbo Tanks are designed to store Oxygen, Nitrogen, and Argon in liquid state, as well as Liquefied Natural Gas.

20,000 to 93,500 Gallons.

PMT 50, 80, 125, 170, 270 lbs/pg2.

Interior Tank: Stainless Steel.

Perlite Isolation.

Technical data									
Model	35000	45000	50000	55000	60000	70000	75000	80000	935000
Water Volume @ 100% gal(L):	38168	49571	53372	59073	64775	76178	79979	85680	98984
	144482	187647	202035	223617	245200	288364	302753	324335	374694
Cold Volume @ 95% gal(L):	35951	46692	50272	55643	61013	71754	75334	80704	93235
	136091	176749	190302	210631	230960	271618	285170	305499	352933
PMT Psig (kg/cm ²):	50 (3.51)		120 (8.43)	150 (10.54)	180 (12.65)	250 (17.57)			
Product:	LIN / LOX / LAR / LNG / ETH								
Dry Weight ± 1 % lb (kg):	91342	113754	120368	123093	138358	155950	162592	171495	193023
	41432	51598	54598	55834	62758	70738	73751	77789	87554
Length (m):	49.50	64.50	69.50	77.00	84.50	99.50	104.50	112.00	129.50
	15.09	19.66	21.18	23.47	25.76	30.33	31.85	34.14	39.47
Width ft (m):	13.67	13.67	13.67	13.67	13.67	13.67	13.67	13.67	13.67
	4.17	4.17	4.17	4.17	4.17	4.17	4.17	4.17	4.17
Tank ft (m):	13.04	13.04	13.04	13.04	13.04	13.04	13.04	13.04	13.04
	3.98	3.98	3.98	3.98	3.98	3.98	3.98	3.98	3.98
Evaporation Percentage (LOX)/dia menor que:	0.27 %	0.26 %	0.25 %	0.24%	0.23 %	0.22 %0	.21 %	0.20 %	0.20 %